

# MATERIAL SAFETY DATA SHEET

## 1. Identification of the substance or mixture and of the supplier

**A. GHS product identifier** FIRSTCLASS TIRE SHIELD PEARL BLACK

**B. Recommended use of the chemical and restrictions on use**

**Recommended use** Tire shine

**Restrictions on use** Use only as intended

**C. Manufacturers**

**Company name** Bullsone

**Address** 7F, Dabong Tower, 418, Teheran-ro Gangnam-gu, Seoul, 135-839, Korea

**Emergency phone number** 822-2106-7777

**Respondent** Han Dong Jin

**Fax** 822-2106-7911

## 2. Hazards identification

**A. GHS classification of the substance/mixture**

Flammable liquids : Category 2

Gases under pressure : Liquefied gas

Reproductive toxicity : Category 2


Specific target organ toxicity (single exposure) : Category 3 (respiratory irritation)

Aspiration hazard : Category 2

Hazardous to the aquatic environment (acute hazard) : Category 3

**B. GHS label elements, including precautionary statements**

**Pictogram and symbol :**



**Signal word :** Danger

**Hazard statements :**

H225 Highly flammable liquid and vapour

H280 Contains gas under pressure; may explode if heated.

H305 May be harmful if swallowed and enters airways.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H402 Harmful to aquatic life.

**Precautionary statements**

**Precaution**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

**Treatment**

P301+P310 If swallowed: Immediately call a poison center or doctor/physician.

P303+P361+P353 If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313 If exposed or concerned: Get medical advice/ attention.

P312 Call a poison center or doctor/physician if you feel unwell.

P331 Do not induce vomiting.

P370+P378 In case of fire: Use extinguisher. for extinction.

**Storage**

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

**Disposal**

P501 Dispose the contents/container in accordance with local/regional/national/international regulations.

**C. Other hazard information not included in hazard classification (NFPA)**

**Health** 2

**Flammability** 1

**Reactivity** Not available

**3. Composition/information on ingredients**

Chemical Name	Common Name(Synonyms)	CAS number	EC number	Content (%)
Isohexane	cyclo-Pentane(CAS No. 287-92-3)			40~50
Hexamethyldisiloxane	HMDS	107-46-0	203-492-7	1~10
secret materials				1~10
Polysiloxane	Dimethylpolysiloxane	63148-62-9	613-156-5	1~10
Isopropyl Myristate		110-27-0	203-751-4	1~5
secret materials				< 1
Reflex rutile glitter pearl R-901E	Synthetic fluorphlogopite (CAS No. 12003-38-2) Tin oxide (CAS No. 18282-10-5) Titanium dioxide (CAS No. 13463-67-7) Synthetic fluorphlogopite (CAS No. 12003-38-2) Tin oxide (CAS No. 18282-10-5) Titanium dioxide (CAS No. 13463-67-7)			< 1
Butane	Butan	106-97-8	203-448-7	10~20
Propane	Dimethylmethan	74-98-6	200-827-9	10~20

**4. First aid measures**

**A. Eye contact**

- Call emergency medical service.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

**B. Skin contact**

- If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Call a poison center or doctor/physician if you feel unwell.
- Call emergency medical service.
- Remove and isolate contaminated clothing and shoes.
- For minor skin contact, avoid spreading material on unaffected skin.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Wash skin with soap and water.

**C. Inhalation**

- If exposed or concerned: Get medical advice/ attention.
- Do not induce vomiting.
- If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other symptoms develop.

**D. Ingestion**

- If swallowed: Immediately call a poison center or doctor/physician.
- Do not induce vomiting.
- Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

**E. Indication of immediate medical attention and notes for physician**

- Exposures require specialized first aid with contact and medical follow-up .
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

<b>5. Fire fighting measures</b>
----------------------------------

**A. Suitable (and unsuitable) extinguishing media**

- Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
- Use dry sand or earth to smother fire.

**B. Specific hazards arising from the chemical**

- Highly flammable liquid and vapour
- Contains gas under pressure; may explode if heated.
- May decompose at high temperatures into forming toxic gases.
- May violently polymerize and result in fire and explosion.
- Vapors may travel to a source of ignition and ignite.
- May form explosive mixtures at temperatures at or above the flashpoint.
- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- Spilled material may create fire or explosion hazard.
- May cause vapor explosion hazard indoors, outdoors or in sewers.
- Some of these materials may burn, but none ignite readily.
- Vapors may form explosive mixtures with air.
- Non-combustible, substance itself does not burn but may decompose upon heating, then produce corrosive and/or toxic fumes.
- Some of these materials, if spilled, may leave a flammable residue after evaporation

**C. Special protective equipment and precautions for fire-fighters**

- Rescuers should put on appropriate protective gear.
- Evacuate area and fight fire from a safe distance.
- Many liquids are lighter than water.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas
- Substance may be transported hot.
- Vapors from liquefied gas are initially heavier than air and spread along ground.

- Substance may be transported in a molten form.
- Ruptured cylinders may rocket.
- Dike fire-control water for later disposal; do not scatter the material.
- Move containers from fire area if you can do it without risk.
- Fire involving Tanks; Do not direct water at source of leak or safety devices; icing may occur.
- Fire involving Tanks; Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Fire involving Tanks; Cool containers with flooding quantities of water until well after fire is out.
- Fire involving Tanks; Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Fire involving Tanks; Always stay away from tanks engulfed in fire.
- Fire involving Tanks; For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.
- Damaged cylinders should be handled only by specialists.
- Use extinguishing agent suitable for type of surrounding fire.

## 6. Accidental release measures

### A. Personal precautions, protective equipment and emergency procedures

- Avoid breathing dust/fume/gas/mist/vapours/spray.
- The very fine particles may cause a fire or explosion, eliminate all ignition sources.
- Clean up spills immediately, observing precautions in Protective Equipment section.
- Eliminate all ignition sources.
- All equipment used when handling the product must be grounded.
- Stop leak if you can do it without risk.
- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- A vapor suppressing foam may be used to reduce vapors.
- Cover with plastic sheet to prevent spreading.
- Prevent dust cloud.
- Please note that there are materials and conditions to avoid.

### B. Environmental precautions and protective procedures

- Prevent entry into waterways, sewers, basements or confined areas.

### C. The methods of purification and removal

- Dike and collect water used to fight fire.
- Absorb spills with inert material (e.g., dry sand or earth), then place in a chemical waste container.
- Absorb the liquid and scrub the area with detergent and water.
- Large Spill; Dike far ahead of liquid spill for later disposal.
- Use clean non-sparking tools to collect absorbed material.
- With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.
- Powder Spill; Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.
- Small Spill; Take up with sand or other non-combustible absorbent material and place into containers for later disposal.

## 7. Handling and storage

### A. Precautions for safe handling

- Do not handle until all safety precautions have been read and understood.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing dust/fume/gas/mist/vapours/spray.
- Use only outdoors or in a well-ventilated area.
- Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

- Follow all MSDS/label precautions even after container is emptied because they may retain product residues.
- Use carefully in handling/storage.
- Loosen closure cautiously before opening.
- All equipment used when handling the product must be grounded.
- Please note that there are materials and conditions to avoid.
- Be careful to heat.
- You need measurement of air concentration and ventilation in low, closed and confined areas due to lack of oxygen.

#### **B. Conditions for safe storage**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Protect from sunlight. Store in a well-ventilated place.
- Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of.
- Containers can build up pressure if exposed to heat (fire).

## **8. Exposure controls/personal protection**

### **A. Occupational Exposure limits**

#### **Korea regulation**

**Isohexane** CAS No. 287-92-3; TWA: 600 ppm ( 1720 mg/m<sup>3</sup> ) / CAS No. 110-54-3; 50 ppm ( 180 mg/m<sup>3</sup> )

#### **ACGIH regulation**

**Hexamethyldisiloxane** 해당 없음.

**Titanium dioxide** : TWA = 10 mg/m<sup>3</sup>

**Butane** STEL 1000 ppm

**Biological exposure index** : Not available

#### **OSHA regulation**

**Titanium dioxide** : TWA = 15 mg/m<sup>3</sup>

**Butane** TWA = 800 ppm, (1900 mg/m<sup>3</sup>)

**Propane** TWA=1000 ppm (1800 mg/m<sup>3</sup>)

#### **NIOSH regulation**

**Butane** TWA = 800 ppm, (1900 mg/m<sup>3</sup>)

**Propane** TWA=1000 ppm (1800 mg/m<sup>3</sup>)

**EU regulation** : Not available

#### **Other**

**Titanium dioxide** : Austria: TWA = 10 mg/m<sup>3</sup> France: TWA = 10 mg/m<sup>3</sup> (as Ti) Italy: TWA = 10 mg/m<sup>3</sup> United Kingdom: TWA = 10 mg/m<sup>3</sup> Russia: TWA = 10 mg/m<sup>3</sup>

**Butane** Germany : TWA=1000ppm(2400 mg/m<sup>3</sup>) Greece : TWA=1000ppm(2350 mg/m<sup>3</sup>) Hong Kong : TWA=800ppm(1900 mg/m<sup>3</sup>)

**Propane** Finland:TWA=800 ppm(1500 mg/m<sup>3</sup>) Germany:TWA=1000 ppm(1800 mg/m<sup>3</sup>) Greece:TWA=1000 ppm(1800 mg/m<sup>3</sup>) Hong Kong:TWA-2500 ppm(4508 mg/m<sup>3</sup>)

### **B. Appropriate engineering controls**

- Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.
- If user operations generate dust, fume, or mist, use ventilation to keep exposure to airborne contaminants below the recommended exposure limit.

### **C. Personal protective equipment**

#### **Respiratory protection**

- Wear NIOSH or European Standard EN 149 approved full or half face piece (with goggles) respiratory protective equipment when necessary.
- In case exposed to gaseous/liquid material, the respiratory protective equipments as follow are recommended. escape full facepiece gas mask (of use for acid gas, in case of acid gas for organic compounds) or escape half facepiece gas mask (of use for acid gas, in case of acid gas for organic compounds) or direct full facepiece gas mask (of use for acid gas, in case of acid gas for organic

compounds) half facepiece gas mask (of use for acid gas, in case of acid gas for organic compounds) or powered air-purifying gas mask.

- In lack of oxygen (< 19.5%), wear the supplied-air respirator or self-contained breathing apparatus.oxygen

#### **Eye protection**

- Wear enclosed safety goggles to protect from gaseous state organic material causing eye irritation or other disorder.

- An eye wash unit and safety shower station should be available nearby work place.

#### **Hand protection**

- Wear appropriate protective gloves by considering physical and chemical properties of chemicals.

#### **Body protection**

- Wear appropriate protective clothing by considering physical and chemical properties of chemicals.

## **9. Physical and chemical properties**

### **A. Appearance**

**Description** Liquid

**Color**

### **B. Odor**

**C. Odor threshold** Not available

**D. pH** Not available

**E. Melting point/freezing point** Not available

**F. Initial boiling point and boiling range** Not available

**G. Flash point** Not available

**H. Evaporation rate** Not available

**I. Flammability (solid, gas)** Not applicable

**J. Upper/lower flammability or explosive limits** Not available

**K. Vapor pressure** Not available

**L. Solubility (ies)** Not available

**M. Vapor density** Not available

**N. Specific gravity** 0.71 +/- 0.05

**O. Partition coefficient: n-octanol/water** Not available

**P. Auto ignition temperature** Not available

**Q. Decomposition temperature** Not available

**R. Viscosity** Not available

**S. Molecular weight** Not available

## **10. Stability and reactivity**

### **A. Chemical stability and Possibility of hazardous reactions:**

- Highly flammable liquid and vapour
- Contains gas under pressure; may explode if heated.
- May decompose at high temperatures into forming toxic gases.
- May violently polymerize and result in fire and explosion.
- May form explosive mixtures at temperatures at or above the flashpoint.
- Containers may explode when heated.
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- Spilled material may create fire or explosion hazard.
- May cause vapor explosion hazard indoors, outdoors or in sewers.
- Some of these materials may burn, but none ignite readily.
- Vapors may form explosive mixtures with air.
- Non-combustible, substance itself does not burn but may decompose upon heating, then produce corrosive and/or toxic fumes.

### **B. Conditions to avoid:**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

### **C. Incompatible materials:**

- Combustibles, reducing agents

**D. Hazardous decomposition products:**

- Corrosive and/or toxic fume
- Irritating, corrosive and/or toxic gases

**11. Toxicological information****A. Information of Health Hazardous:****Acute toxicity**

**Oral** [Not classified] (ATEmix = 128,055.56 mg/kg bw)

- **Isohexane** : Rat LD<sub>50</sub> = mg/kg
- **Hexamethyldisiloxane** : Guinea pig = 50,000 mg/kg
- **KP-550** : Rat LD<sub>50</sub> > 2,000 mg/kg
- **Polysiloxane** : Rat LD<sub>50</sub> > 5,000 mg/kg
- **Isopropyl Myristate** : Rat LD<sub>50</sub> > 79,500 mg/kg

**Dermal** [Not classified]

- **Polysiloxane** : Rabbit LD<sub>50</sub> > 10,000 mg/kg Acute toxicity is very low
- **Isopropyl Myristate** : Rabbit LD<sub>50</sub> > 5,000 mg/kg
- **Phenyl silicone resin** : Rabbit LD<sub>50</sub> > 2,000 mg/kg

**Inhalation** [Not classified] (ATEmix = 32.78 mg/L)

- **Isohexane** : Rat LD<sub>50</sub> = mg/kg LC50 > 14.35 mg/ℓ 4hr Rat(as cyclo=Pentane) / LC50 77,000 ppm 1hr(as normal-Hexane)
- **Polysiloxane** : Rat LC<sub>50</sub> > 535 mg/L Acute toxicity is very low
- **Phenyl silicone resin** : Mouse LC<sub>50</sub> = 0.467 mg/L/4hr (Fatal if inhaled of mist/spray)
- **Butane** : Rat LC<sub>50</sub> = 1,443 mg/L/15min
- **Propane** : Rat LC<sub>50</sub> = 280,000 mg/kg/10min

**Skin corrosion/ irritation** [Not available]

- **Isohexane** : - In skin irritation test with rabbits and human, observed skin irritation.
- **Hexamethyldisiloxane** : Skin inflammation - Rabbit
- **Polysiloxane** : In test on skin irritation with rabbits, skin irritations were not observed.
- **Isopropyl Myristate** : - Slight skin irritation is seen in rabbits(24hr) - Slight skin irritation(human, 3hr)
- **Phenyl silicone resin** : No significant irritation is expected from a single, short-term exposure.

**Serious eye damage/ irritation** [Not available]

- **Isohexane** : - In eye irritation test with rabbits and human, observed eye irritation.
- **Polysiloxane** : In test on eyes irritation with rabbits, eyes irritations were not observed.
- **Isopropyl Myristate** : Slightly irritation to rabbit eyes (undiluted)
- **Phenyl silicone resin** : Direct contact may cause temporary redness and discomfort.

**Respiratory sensitization** [Not available]

**Skin sensitization** [Not classified]

- **Polysiloxane** : In skin sensitisation test with animals, skin sensitization were not observed.
- **Isopropyl Myristate** : Skin sensitising effects were not observed in guinea pigs and humans.

**Carcinogenicity** [Not classified]

**IARC**

- : Titanium dioxide : Group 2B

**ACGIH**

- : Titanium dioxide : A4

**KOREA-ISHL**

- : Titanium dioxide : 2

**Isopropyl Myristate** : No component of this product presents at levels greater than or equal 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**Mutagenicity** [Not classified]

- **Polysiloxane** : Ames test results negative
- **Butane** : Negative reactions were observed with and without metabolic activation in vitro(mammalian chromosome aberration test(OECD TG 473, GLP), bacterial reverse mutation assay(OECD TG 471, GLP).
- **Propane** : Negative reactions were observed with and without metabolic activation in vitro(mammalian chromosome aberration test(OECD TG 473, GLP), bacterial reverse mutation assay(OECD TG 471, GLP).

#### Reproductive toxicity [Category 2]

- **Butane** : In reproduction/developmental toxicity screening test, there were no significant adverse effects on reproductive parameters and no evidence of malformations at any doses.(NOAEC=21641 mg/m<sup>3</sup>)(OECD TG 422, GLP)
- **Propane** : In reproduction/developmental toxicity screening test, there were no significant adverse effects on reproductive parameters and no evidence of malformations at any doses.(NOAEC = 9000 ppm)(OECD TG 422, GLP)

#### Specific target organ toxicity (single exposure) [null] [구분 3 (호흡기계 자극)]

- **Phenyl silicone resin** : Low ingestion hazard in normal use.
- **Propane** : In acute inhalation toxicity test with rats, acute toxic effects were not observed.

#### Specific target organ toxicity (repeat exposure) [Not classified]

- **Phenyl silicone resin** : Repeated ingestion or swallowing large amounts may cause internal injuries.
- **Butane** : In repeated inhalation toxicity study with rats for 28 days, repeated toxicity related effects were not observed.(NOAEC = 9,000 ppm)(OECD TG 422, GLP)
- **Propane** : In repeated inhalation toxicity study with rats for 28 days, repeated toxicity related effects were not observed.(OECD TG 422, GLP)

#### Aspiration Hazard [Category 2]

## 12. Ecological information

### A. Ecological toxicity

- Acute toxicity : [Category 3] (ATEmix = 76.34780mg/ℓ)
- Chronic toxicity : [Not available]

#### Fish

- **Isohexane** : 96hr-LC<sub>50</sub> = 4656 mg/L
- **Isopropyl Myristate** : LC<sub>50</sub> = 8400 mg/L ISO 7346/2 (semi-static)
- : Titanium dioxide : 96hr-LC<sub>50</sub> (Oncorhynchus mykiss) > 100 mg/L
- **Propane** : 96hr-LC<sub>50</sub> = 27.98 mg/L (Estimated)

#### crustacean

- **Isohexane** : 48hr-LC<sub>50</sub> = 5424 mg/L
- **Isopropyl Myristate** : EC<sub>50</sub> > 100 mg/L
- : Titanium dioxide : 48hr-LC<sub>50</sub> (Daphnia magna) ≥ 100 mg/L (OECD TG 202, GLP), 25d-NOEC(Daphnia magna) ≥ 70 mg/L
- **Propane** : 48hr-LC<sub>50</sub> = 14.22 mg/L (Estimated)

#### Algae

- **Isohexane** : 96hr-EC<sub>50</sub> = 3635 mg/L
- **Hexamethyldisiloxane** : 96hr-ErC<sub>50</sub> > 0.55 mg/L (OECD TG 201)
- : Titanium dioxide : 72hr-EC<sub>50</sub> (Scenedesmus subspicatus) = 61 mg/L (EPA-600/9-78-018), 72hr-NOEC(Scenedesmus subspicatus) = 1 mg/L
- **Propane** : 96hr-EC<sub>50</sub> = 7.71 mg/L (Estimated)

### B. Persistence and degradability

#### Persistence

- **Isohexane** : Low persistency (log Kow is less than 4 estimated.) (Log Kow = 3.21)
- **Isopropyl Myristate** : High persistency (log Kow is more than 4 estimated.) (Log Kow = 3.3 ~ 6)
- **Propane** : Low persistency (log Kow is less than 4 estimated.) (Log Kow = 2.8) (pH 7)(20 °C)

#### Degradability

- **Phenyl silicone resin** : - Siloxane is degraded in soil. - Additional environmental information on the silicone component can be provided on request.



### C. Bioaccumulative potential

#### Bioaccumulation

- **Isohexane** : Bioaccumulation is expected to be low according to the BCF < 500 (BCF = 100 ~ 408)
- **Phenyl silicone resin** : Accumulation in organisms is unlikely.
- : **Titanium dioxide** : Bioaccumulation is expected to be low according to the BCF < 500 (BCF = 13.73) (estimated)

#### Biodegradation

- **Isopropyl Myristate** : As well-biodegraded, it is expected to have low accumulation potential in living organisms (= 91% biodegradation was observed after 30 days) (Directive 84/449/EEC)
- **Butane** : As well-biodegraded, it is expected to have low accumulation potential in living organisms (= 100% biodegradation was observed after 385 hrs)
- **Propane** : As not well-biodegraded, it is expected to have high accumulation potential in living organisms (= 50% biodegradation was observed after 2 days) (Q)SAR

#### D. Mobility in soil

Not available

#### E. Other hazardous effect

- **Phenyl silicone resin** : - Recent study shows that rats exposed via inhalation to aerosol of trimethyl phenyl silsesquioxane display a high order of toxicity (4 hour LC50=0.47 mg/l). These responses have not been observed in animals exposed via other routes (oral ingestion and dermal). - Siloxanes are removed from water by sedimentation or binding to sewage. - No adverse effects on bacterial. More than 90% are removed by binding to sewage sludge. The siloxanes in this product do not contribute to the biochemical oxygen demand (BOD).

## 13. Disposal considerations

### A. Disposal method

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

### B. Disposal precaution

Consider the required attentions in accordance with waste treatment management regulation.

## 14. Transport information

A. UN Number 1950

B. UN Proper shipping name AEROSOLS

C. Transport Hazard class 2

D. Packing group No

E. Marine pollutant

F. Special precautions

in case of fire F-D

in case of leakage S-U

## 15. Regulatory information

### A. Occupational Safety and Health Regulation

**Isohexane** : Occupational exposure limits listed

**Isohexane** : Authorization subject listed CAS No. 110-54-3

**Isohexane** : Administration subject listed CAS No. 110-54-3

**Isohexane** : Work environment monitoring listed CAS No. 110-54-3; (6 months)

**Isohexane** : Health examination agent CAS No. 110-54-3; (12 months)

: Administration subject listed ;CAS No. 13463-67-7

: Occupational exposure limits listed ;CAS No. 13463-67-7

: Work environment monitoring listed ;CAS No. 13463-67-7(6 months)

: Occupational exposure limits listed

**Butane** : Occupational exposure limits listed

### B. Toxic Chemical Control Act

**Isohexane** : Existing Chemical Substance CAS No. 287-92-3; KE-09297/ CAS No. 107-83-5; KE-24699/ CAS No. 110-54-3; KE-18626

**KP-550** : Existing Chemical Substance Existing Chemical Substance ; CAS No. 31807-55-3: KE-21511

**Polysiloxane** : Existing Chemical Substance (KE-31068)

: Existing Chemical Substance ; CAS No. 12003-38-2: KE-17066/ CAS No. 13463-67-7:KE-33900

#### C. Dangerous Material Safety Management Regulation

**Isohexane** : Dangerous Material Safety Management Regulation CAS No. 287-92-3; Petroleum class 4-1 (non-water soluble liquid) 200ℓ / CAS No. 107-83-5; Petroleum class 4-1 (non-water soluble liquid) 200ℓ / CAS No. 110-54-3; Petroleum class 4-1 (non-water soluble liquid) 200ℓ

**Hexamethyldisiloxane** : Dangerous Material Safety Management Regulation 200ℓ

**KP-550** : Dangerous Material Safety Management Regulation CAS No. 31807-55-3; Petroleum class 4-2 (non-water soluble liquid) 1000ℓ

**Phenyl silicone resin** : Dangerous Material Safety Management Regulation 2000ℓ

: Dangerous Material Safety Management Regulation ; CAS No. 13463-67-7: Non-dangerous goods

#### D. Wastes Control Act

: Wastes Control Act Controlled wastes; CAS No. 12003-38-2

#### E. Other regulation (internal and external)

##### Internal information

**Persistent Organic Pollutants Acts** Not regulated

##### External information

##### EU classification(classification)

**Butane** : Classification F+; R12

**Propane** : Classification F+; R12

##### EU classification(risk phrases)

**Butane** : Hazard statements R12

**Propane** : Hazard statements R12

##### EU classification(safety phrases)

**Butane** : Precautionary statements S2, S9, S16

**Propane** : Precautionary statements S2, S9, S16

**EU SVHC list** Not regulated

**EU Authorisation List** Not regulated

##### EU Restriction list

**Propane** : EU Restriction list Regulated

**U.S.A management information (OSHA Regulation)** Not regulated

**U.S.A management information (CERCLA Regulation)** Not regulated

**U.S.A management information (EPCRA 302 Regulation)** Not regulated

**U.S.A management information (EPCRA 304 Regulation)** Not regulated

**U.S.A management information (EPCRA 313 Regulation)** Not regulated

**Substance of Rotterdam Protocol** Not regulated

**Substance of Stockholm Protocol** Not regulated

**Substance of Montreal Protocol** Not regulated

#### Foreign Inventory Status

##### Hexamethyldisiloxane

U.S.A management information Section 8(b) Inventory (TSCA): Present

Japan management information Existing and New Chemical Substances (ENCS): Present

China management information Inventory of Existing Chemical Substances (IECSC): Present

Canada management information Domestic Substances List (DSL): Present

Australia management information Inventory of Chemical Substances (AICS): Present

Philippines management information Inventory of Chemicals and Chemical Substances

(PICCS): Present

##### KP-550

U.S.A management information Section 8(b) Inventory (TSCA): (CAS No. 31807-55-3); Present

Japan management information Existing and New Chemical Substances (ENCS): (CAS No. 31807-55-3); (2)-10

China management information Inventory of Existing Chemical Substances (IECSC): (CAS No. 31807-55-3); Present 40744

Canada management information Domestic Substances List (DSL): (CAS No. 31807-55-3); Present

Australia management information Inventory of Chemical Substances (AICS): (CAS No. 31807-55-3); Present

Philippines management information Inventory of Chemicals and Chemical Substances (PICCS): (CAS No. 31807-55-3); Present

New Zealand management information Inventory of Chemicals (NZIoC): (CAS No. 31807-55-3); May be used as a component in a product covered by a group standard but it is not approved for use as a chemical in its own right.

#### **Polysiloxane**

U.S.A management information Section 8(b) Inventory (TSCA): Present [XU]

Japan management information Existing and New Chemical Substances (ENCS): (7)-476

China management information Inventory of Existing Chemical Substances (IECSC): Present 08512

Canada management information Domestic Substances List (DSL): Present

Australia management information Inventory of Chemical Substances (AICS): Present

New Zealand management information Inventory of Chemicals (NZIoC): Inventory of Chemicals (NZIoC): HSNO Approval: HSR003036

Philippines management information Inventory of Chemicals and Chemical Substances (PICCS): Present

#### **Isopropyl Myristate**

U.S.A management information Section 8(b) Inventory (TSCA): Present

Japan management information Existing and New Chemical Substances (ENCS): 2-798

China management information Inventory of Existing Chemical Substances (IECSC): Present

Canada management information Domestic Substances List (DSL): Present

Australia management information Inventory of Chemical Substances (AICS): Present

Philippines management information Inventory of Chemicals and Chemical Substances (PICCS): Present

#### **Phenyl silicone resin**

U.S.A management information Section 8(b) Inventory (TSCA): Present

Japan management information Existing and New Chemical Substances (ENCS): Present

China management information Inventory of Existing Chemical Substances (IECSC): Present

Canada management information Domestic Substances List (DSL): Present

Australia management information Inventory of Chemical Substances (AICS): Present

Philippines management information Inventory of Chemicals and Chemical Substances (PICCS): Present

U.S.A management information Section 8(b) Inventory (TSCA): Present ; CAS No. 12003-38-2/ CAS No. 13463-67-7

Japan management information Existing and New Chemical Substances (ENCS): Existing and New Chemical Substances (ENCS): (5)-5225, (1)-558 ; CAS No. 13463-67-7

China management information Inventory of Existing Chemical Substances (IECSC): Present ; CAS No. 12003-38-2/ CAS No. 13463-67-7

Canada management information Domestic Substances List (DSL): Present ; CAS No. 12003-38-2/ CAS No. 13463-67-7

Australia management information Inventory of Chemical Substances (AICS): Present ; CAS No. 12003-38-2/ CAS No. 13463-67-7

Philippines management information Inventory of Chemicals and Chemical Substances (PICCS): Present ; CAS No. 12003-38-2/ CAS No. 13463-67-7

New Zealand management information Inventory of Chemicals (NZIoC): May be used as a component in a product covered by a group standard but it is not approved for use as a chemical in its own right; CAS No. 12003-38-2/ Inventory of Chemicals (NZIoC): May be used as a single component chemical under an appropriate group standard. ; CAS No. 13463-67-7

European management information European inventory of existing commercial chemical substances(EINECS): 234-426-5; CAS No. 12003-38-2/ (EINECS):236-675-5 ; CAS No. 13463-67-7

#### **Butane**

U.S.A management information Section 8(b) Inventory (TSCA): Present

Japan management information Existing and New Chemical Substances (ENCS): (2)-4

China management information Inventory of Existing Chemical Substances (IECSC): Present  
41372

Canada management information Domestic Substances List (DSL): Present

Australia management information Inventory of Chemical Substances (AICS): Present

New Zealand management information Inventory of Chemicals (NZIoC): HSNO Approval:  
HSR000989

Philippines management information Inventory of Chemicals and Chemical Substances  
(PICCS): Present

#### **Propane**

U.S.A management information Section 8(b) Inventory (TSCA): Present

Japan management information Existing and New Chemical Substances (ENCS): (2)-3

China management information Inventory of Existing Chemical Substances (IECSC): Present  
03571

Canada management information Domestic Substances List (DSL): Present

Australia management information Inventory of Chemical Substances (AICS): Present

New Zealand management information Inventory of Chemicals (NZIoC): HSNO Approval:  
HSR001010

Philippines management information Inventory of Chemicals and Chemical Substances  
(PICCS): Present

## **16. Other information**

### **A. Information source and references**

DOW CORNING MSDS

Emergency Response Guidebook 2008;

[http://phmsa.dot.gov/staticfiles/PHMSA/DownloadableFiles/Files/erg2008\\_eng.pdf](http://phmsa.dot.gov/staticfiles/PHMSA/DownloadableFiles/Files/erg2008_eng.pdf)

National Emergency Management Agency-Korea dangerous material inventory management system;

<http://www.nema.go.kr/hazmat/main/main.jsp>

Korea Occupational Health & Safety Agency; <http://www.kosha.net>

GREENWELL MSDS

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans; <http://monographs.iarc.fr>

Dongsung Highchem MSDS

National Chemicals Information System; <http://ncis.nier.go.kr/ncis/>

TOMES-LOLI®; <http://www.rightanswerknowledge.com/loginRA.asp>

Waste Control Act enforcement regulation attached [1]

The Chemical Database -The Department of Chemistry at the University of Akron;

<http://ull.chemistry.uakron.edu/erd/>

Shin etsu MSDS

CQV MSDS

National Toxicology Program; [http://ntp-apps.niehs.nih.gov/ntp\\_tox/index.cfm](http://ntp-apps.niehs.nih.gov/ntp_tox/index.cfm)

NIOSH Pocket Guide; <http://www.cdc.gov/niosh/npg/npgdcas.html>

American Conference of Governmental Industrial Hygienists TLVs and BEIs.

REACH information on registered substances; <http://apps.echa.europa.eu/registered/registered-sub.aspx>

Momentive MSDS

EU CLP; <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>

Momentive Performance materials MSDS

UN Recommendations on the transport of dangerous goods 17th

### **B. Issuing date 2014.06.13.**

### **C. Revision number and date**

**revision number**

**date of the latest revision**

### **D. Others**

- Revised Material Safety Data Sheet based on the amendments made on the Ministry of Employment and Labor Public Notice on Standard for Classification Labeling of Chemical Substance and Material Safety Data Sheet.

- This MSDS is authored in pursuant to the Article 41 of the Occupational Safety and Health Act.

- The content is based on the latest information and knowledge that we currently possess.

- This MSDS was authored to aid buyer, processor or any other third person who handles the chemical of subject in the MSDS; additionally, it does not warrant suitability of the chemical for special purposes or the commercial use of statements that approves the use of it in combination with other chemicals as well as technical or legal liabilities.
- The content of the MSDS may vary depending on the country or the region and may not coincide with the actual regulations. Therefore, the buyer or the processor of the chemical is responsible for observing responsible government's or the region's regulations.